

## Provisional Data Sheet

### PRODUCT DESCRIPTION

**Genable 3105** is an optimised dispersion of graphene nanoplatelets and non-metallic ion-exchange pigment, stabilised in epoxy resin (EEW = 250g/eq.).

**Genable 3105** is a metal-free, graphene-enhanced, active, anti-corrosion additive offering outstanding performance in industrial coatings on steel and aluminium substrates.

### PRODUCT INFORMATION

<b>Appearance</b>	Black liquid
<b>Matrix</b>	Epoxy Resin (EEW = 250g/eq)
<b>Density (g/ml)</b>	1.0 – 1.4
<b>Viscosity (Pa.s)</b>	< 10
<b>Particle Size - D90 (microns)</b>	< 25
<b>Shelf-Life</b>	9 Months

### USAGE

This dispersion is produced using AGM's proprietary manufacturing processes. The product is optimised to be incorporated into industry systems under medium shear. Please ensure that following the addition of the dispersion the system is fully homogenised.

### DIRECTIONS OF USE

Please stir well before use. The dispersion may develop slight sedimentation during transport or storage. If this is the case the dispersion can be recombined by mechanical mixing.

### STORAGE

Store in accordance with local regulations. The product should be stored in the original container, at room temperature (ideally, >20°C), in a dry, well-ventilated location away from direct sunlight. Keep away from incompatible materials and food and drink. Keep the container tightly sealed.

### SAFETY

Wear appropriate PPE. Use the minimum quantity of product required for a particular process. Use only in well-ventilated areas, preferably in an enclosed system. Provide appropriate exhaust ventilation at places where aerosols/dust may be formed. Handle and open the container with care. Keep in the original container or an approved alternative made from a compatible material. Always close containers tightly after removal of the product. Empty containers retain product residue and can be hazardous. Do not re-use the container. Dispose of materials in accordance with local regulations.